

# METAPACE

# T-1



## Specifications

|                         |   |
|-------------------------|---|
| <b>Printing Method</b>  | Direct Thermal  |
| <b>Equipment</b>        | Autocutter, 2 connections for cash drawers, Paper Near End/End Sensor   |
| <b>Colour</b>           | Black or White  |
| <b>Printing Speed</b>   | 150 mm/s  |
| <b>Roll Changes</b>     | Easy Paper Drop-In (single-handed and without contriving)               |
| <b>Resolution</b>       | 7 Dot/mm (180 dpi)  |
| <b>Character Set</b>    | Alphanumeric: 96 characters   |
| <b>Extended Graphic</b> | 128 x 7 Pages (1 space page)  |
| <b>Character Size</b>   | Size: Font A: 12 x 24, Font B: 9 x 17; per line: Font A: 42, Font B: 56 |
| <b>Consumables</b>      | Thermal paper   |
| <b>Paper</b>            | Width: max. 83 mm, Core: max. 19 mm                                     |
| <b>Durability</b>       | 100 km TPH (direct thermal printhead), 1,5 million cuts (Autocutter)    |
| <b>Flash Memory</b>     | 16 Mbit   |
| <b>Memory for logos</b> | 256 KB (NV RAM)   |
| <b>Barcodes</b>         | EAN-13, EAN-8, Code 39, Code 93, Code 128, ITF, Coda bar, UPC-A, UPC-E  |
| <b>Emulation</b>        | ESC/POS   |
| <b>Driver</b>           | Windows 95/98/Me/2000/NT/XP/2003 Server, OPOS                           |
| <b>Sensors</b>          | Paper end, Paper Near end, Wall Mounting Near end, Cover Open           |
| <b>Memory</b>           | 8 KB printer buffer, 256 KB memory for logos (NV RAM)                   |
| <b>Interfaces</b>       | RS232C, parallel, USB; Ethernet, BT, DUAL (serial/USB) optional         |
| <b>Options</b>          | Wallmount   |
| <b>Power supply</b>     | AC120V-230V +/- 10 %, DC24V, 2,3A                                       |
| <b>Dimensions (mm)</b>  | 145 (W) x 195 (L) x 146 (H)   |
| <b>Warranty</b>         | 60 months   |

Hanka Kantoormachines bv  
Boschstraat 150  
4811 GL Breda

Tel: 076-5155077  
Fax: 076-5155078

[www.hanka.nl](http://www.hanka.nl)