

2nd generation Impact Printer

# SRP-275



**The SRP-275 is 2nd generation Impact printer which sets you free from embarrassing paper jams.**

This printer has more functions such as two-color printing and versatile paper roll sizes and boasts about fast speed and less printing noise. It's really successful series from the SRP-270. Also the SRP-275 is ideal for both POS receipt printing and remote hospitality printing. It is a robust, high performance impact receipt printer which is exceptionally easy to use. Featuring drop-in paper loading, selectable auto-cutter and clamshell covers for easy access and maintenance, the SRP-275 is very reliable and prints on plain paper in three widths.

2nd generation Impact Printer

# SRP-275




Ivory Dark Gray

SRP-275 A  
(Tear-bar Type)

SRP-275 C  
(Auto Cutter Type)

Easy Paper Loading



Built-in Power Supply



Variable Paper Width



### SPECIFICATION FOR THE SRP-275 IMPACT PRINTER

PRINT	PRINT METHOD	9 pin serial impact dot matrix
	PRINT DIRECTION	Bi-directional, Logic seeking, Friction feed
	PRINT SPEED	5.1 lines per second at 40 column
	PAPER SUPPLY METHOD	Drop in and print
	DOT PITCH	0.352mm (1 / 72")
	DOT WIRE DIAMETER	0.3mm (0.01")
	CHARACTERS PER LINE	Font A : 33 Font B : 40
	PRINTING WIDTH	63.34mm (2.49")
	LINE SPACING	4.233mm (1 / 6 inch), Can be set by a command
	CHARACTER FONT	Font A : 9 x 9 Font B : 7 x 9
	CHARACTER SETS	Alphanumeric characters : 95, international characters : 48, Extended graphics : 128 x 20 pages
	MEMORY	Print buffer : 8 Kbytes, NV image : 256 Kbytes
	CONTROL CODE EMULATION	ESC / POS, Star, Citizen.
SOFTWARE	Utilities : Firmware / NV image download, Virtual memory switchmanager	
DRIVERS	Windows 95 / 98 / ME / 2000 / NT4.0 / XP / 2003 server, OPOS	
SENSORS	Paper end, paper near end, wall mounting paper near end, cover open	
BUZZER	Buzzer alarm	
PAPER ROLL	WIDTH	76, 69, 57 ± 0.5mm, 2.99", 2.74", 2.26" ± (0.22")
	THICKNESS	0.06 - 0.09mm (0.002 - 0.003")
	DIAMETER	83mm (3.27") - Core Max.19mm
RIBBON	TYPE	RRC-201 B/R (black / red), RRC-201 B (black), RRC-201 P (purple)
RELIABILITY	MCBF	18 million lines
	AUTO CUTTER	1.5 million cuts
	DKD FUNCTION	2 ports
CONNECTIVITY	INTERFACE	Serial, Parallel, USB, Ethernet(10 / 100 Base-t), bluetooth
	EMC / SAFETY STANDARD	CE, FCC, UL, TUV, GS
	SUPPLY	AC100V-240V ± 10%, DC24V, 1.5A Internal / External installation
POWER	PAPER CUTTER	SRP-275A (tear bar), SRP-275C (auto cutter)
	COLOR	Ivory, Dark Gray
	WALL MOUNT	Wall mount bracket
	LANGUAGE	Buyer language support

**Hanka Kantoormachines bv**  
Boschstraat 150  
4811 GL Breda

Tel: 076-5155077  
Fax: 076-5155078

[www.hanka.nl](http://www.hanka.nl)