



EXPLOR@

VX D

Explor@VX D is a multi-functional touch screen POS designed for multi-purpose; mainly addressed to the **hospitality** and **catering** use. **LED True Flat** display with adjustable tilt, USB ports, cash drawer management, small footprint optimize operational flexibility. The use of **SSD** (Solid State Disk) is able to ensure greater reliability in terms of strenght and greater speed in the stages of data access. With its compact, stylish and **vertical** design is suitable for any environment and use.

- MULTI-FUNCTIONAL TOUCH-SCREEN POS**
- BEST OPERATIONS WITH SSD (SOLID STATE DISK)**
- ADJUSTABLE VIEW ANGLE LED**
- TRUE FLAT DISPLAY**
- EASY ACCESS TO KEY COMPONENTS**
- IDEAL FOR HOSPITALITY AND CATERING**
- THANKS TO PROTECTION AGAINST DUST AND WATER (IP54)**



MULTI-FUNCTIONAL TOUCH-SCREEN POS



Tool free access to SSD (Solid State Disk)



Magnetic Card Reader (optional)



Customer display VFD 2 x 20 or second LCD display (optionals)

TECHNICAL SPECIFICATIONS

MOTHERBOARD

Processor	Intel Atom D2550 Dual Core 1.86 GHz, L2 1M, 10W
Chipset	INTEL NM10
System Memory	DDR3 - 1 socket, up to 4 GB SO-DIMM FSB 1066MHz
Graphic Memory	IDX9, Graphic core speed at 640MHz
Expansion	Mini PCI-E socket

LCD/TOUCH PANEL

LCD size	15" LED LCD
Brightness (nits)	300
Resolution	1024 x 768
Touch screen type	ELO Resistive (5 wires)
Tilt angle	0° ~ 80°

STORAGE AND EXTERNAL I/O PORTS

SSD (Solid State Disk)	2,5" SATA-2 (min 32 GB)
Control/Indicator	Power button Power LED
Rear I/O	Serial/COM: 4 ports COM RJ-45: COM1 standard RS-232 not powered; COM2/3/4 powered RS232 (enable/disable by BIOS: COM2 default 0, COM3 default 5V COM4 default 12V) USB: 4 ports (V2.0) Parallel port: 1 LAN (10/100/1000): 1 x RJ45 Cash drawer: 1 x RJ11 (12V/19V) VGA output: 1 Jack DC: 1

ENVIRONMENT

EMC & Safety	Class A, CE
Power supply	External power adapter 19V/65W
Operating Temperature	0° C ~ 35° C
Storage Temperature	-20° C ~ 60° C

OPZIONI

MSR	MSR 3 tracks (PS/2)
2 in 1 MSR	MSR (PS/2) + fingerprint (USB) MSR (PS/2) + i-Button (PS/2)
Customer Display	VFD 2 x 20 characters (COM)
Second Display	8.4"/15" LCD without touch

VARIOUS

Operating systems supported	POSReady 7, POSReady 2009, Windows XP, XP Embedded, Windows 7, Linux
Dimensions (LxPxA)	365 x 220 x 368 mm (with LCD 80°)
Weight	9 kg

Product performances are referred to an appropriate use under optimal conditions. With the right to change technical specifications. The registered trademarks are the property of their respective owners. EXPLOR@VX D is distributed by Olivetti S.p.A. (02/14) - Code: 29120-00