## Explor@ 460 POS Touchscreen

**Explor@ 460** is the new **compact and elegant** Olivetti Point of Sale terminal, suitable for any kind of **professional and commercial environments**: fashionable shops, hotels, restaurants and business.

The **new 15" TFT flat-bezel** multi-touch screen offers the advantage of a **surface easy to clean** and **IP65 std** guarantees protection against dust and splashing water.

The **integrated connectivity** with retail peripherals optimizes the operational **flexibility**.

The **new generation Intel® Bay Trail platform** offers advanced performances.

STYLISH, COMPACT DESIGN LOWER POWER CONSUMPTION SUPPORTED 15" 2ND DISPLAY AND 2 X 20 CUSTOMER DISPLAY WIDE I/O CONNECTIONS FOR VARIOUS PERIPHERALS











Elegant design and stable round base

Tiltable display 0°- 90°

## **TECHNICAL SPECIFICATIONS**

MOTHERBOARD	
CPU	Intel® Bay Trail-Mobile/Desktop SoC
	Processor: Celeron® J1900 (4 cores,
	up to 2.42 GHz, max. TDP 10 Watt)
Graphic	Intel® HD Graphics
System Memory	1 x SO-DIMM DDR3L 1067/1333MHz
	Standard memory: 4 Gb, upgradable
	to 8 Gb
Cooling Solution	Fan-less
Compatible OS	Windows® Embedded POSReady 7,
	Windows® 7, Professional for Embedded
	Systems, Windows® Embedded 8.1
	Industry Pro, Win10 IoT

I/O PORTS	
Serial	2xRJ50, 1xDB9
	1 additional DB9 in place of VGA port (optional)
USB	USB 2.0 x 4
	USB 3.0 x 1
LAN	Gigabit Ethernet by RJ-45 x 1, support Wake on LAN
Cash Drawer	RJ12 x 1, support 12V / 19V DC cash drawer
Audio	2 W Speaker x 2
VGA	DB15 (can be replaced by a fourth serial port)
DP / HDMI	Mini Display Port x 1 (supporting active converter
	cable to VGA, DVI, HDMI)
DC-in	19VDC input x 1, 2pins jack
DC-out	12VDC x 1/1A output

15" TFT LCD Panel
250 cd/m2
1024 x 768
LED
Bezel-Free
0°~90°
10-points P-CAP type

VARIOUS	
Color	Black / Silver
Material	Plastic / Aluminium
Certifications	CE / WEEE / RoHS
Dimension (WxDxH)	36.5 x 28 x 32.8 cm (14.3x11x13 inch)
Net Weight / Gross Weight	6.8kg, 15.1lb / 8.8 kg, 19.6lb
Operation Temperature	0 to 40°C
Storage Temperature	-20 ~ 60°C
Humidity	20% to 85% RH (non condensing)

## **SOTRAGE DEVICE**

Interface HDD / SSD SATA (3.0Gb/S)x1 + 1mSATA slot 320 Gb 2.5" SATA replaceable by factory by 64Gb SSD

Performance relates to use of the product under optimal conditions. Right reserved to modify technical specifications. Registered trademarks are the property of their respective owners. EXPLOR@ 460 is distributed by Olivetti S.p.A. (05/2017) - Code: 49489-01-w

OLIVETTI S.P.A. VIA JERVIS 77 10015 IVREA (TO) ITALIA www.olivetti.com